## **Product Information Sheet**

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

## Supplier's name or trade mark: LEDVANCE

Supplier's address: LEDVANCE GmbH, Parkring 33, Garching, Germany

## Model identifier: AC34683

## Type of light source:

Lighting technology used:	LED	Non-directional or directional:	NDLS
Light source cap-type	constant		
(or other electric interface)	current: 700 mA		
Mains or non-mains:	NMLS	Connected light source (CLS):	No
Colour-tuneable light source:	No	Envelope:	-
High luminance light source:	No		
Anti-glare shield:	No	Dimmable:	No

Product parameters							
Parameter		Value	Parameter	Value			
General product parameters:							
Energy consump mode (kWh/100 up to the nearest	0 h), rounded	27	Energy efficiency class	E			
Useful luminous indicating if it ref in a sphere (360 cone (120º) or in (90º)	fers to the flux D <sup>o</sup> ), in a wide	3 500 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	3 000			
On-mode po expressed in W	ower (P <sub>on</sub> ),	27,0	Standby power (P <sub>sb</sub> ), expressed in W and rounded to the second decimal	0,00			
Networked stand for CLS, express rounded to the se	ed in W and	-	Colour rendering index, rounded to the nearest integer, or the range of CRI- values that can be set	80			
Outer	Height	699	Spectral power	See image			
	Width	9	distribution in the	in last page			
without	Depth	1	1	Page 1 / 3			

separate control gear, lighting control parts and non- lighting control parts, if any (millimetre)		range 250 nm to 800 nm, at full-load	
Claim of equivalent power <sup>(a)</sup>	-	If yes, equivalent power (W)	-
		Chromaticity coordinates (x and y)	0,440
Parameters for LED and OLED lig	ht sources:	· · · · · · · · · · · · · · · · · · ·	
R9 colour rendering index value	0	Survival factor	0,90
the lumen maintenance factor	0,96		
(a),	1		

(a)<sub>'-'</sub> : not applicable;

(b)'-' : not applicable;

