Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

| sources | | | | | | |
|--|-----------------|------------------------------|--|--------------|--|--|
| Supplier's name or trade mark: LEDVANCE | | | | | | |
| Supplier's address: LEDVANCE GmbH, Parkring 33, Garching, Germany | | | | | | |
| Model identifie | r: AC34883 | | | | | |
| Type of light so | urce: | | | | | |
| Lighting technol | logy used: | LED | Non-directional or directional: | DLS | | |
| Light source cap-type (or other electric interface) | | constant current: 89 mA | | | | |
| Mains or non-m | iains: | NMLS | Connected light source (CLS): | No | | |
| Colour-tuneable | e light source: | No | Envelope: | - | | |
| High luminance | light source: | No | | | | |
| Anti-glare shield: | | No | Dimmable: | No | | |
| Product parameters | | | | | | |
| Parameter | | Value | Parameter | Value | | |
| General product parameters: | | | | | | |
| Energy consumption in on- mode (kWh/1000 h), rounded up to the nearest integer | | 18 | Energy efficiency class | F | | |
| Useful luminous flux (фuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°) | | 1 480 in Wide cone (120°) | Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set | 3 000 | | |
| On-mode power (P _{on}), expressed in W | | 18,0 | Standby power (P _{sb}), expressed in W and rounded to the second decimal | 0,00 | | |
| Networked standby power (P _{net}) for CLS, expressed in W and rounded to the second decimal | | - | Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set | 80 | | |
| Outer | Height | 98 | Spectral power | See image | | |
| dimensions without | Width | 70 | distribution in the | in last page | | |
| without | Depth | 8 | | | | |

| separate control gear, lighting control parts and non- lighting control parts, if any (millimetre) | | range 250 nm to 800 nm, at full-load | | | | |
|--|------|--|-------|--|--|--|
| Claim of equivalent power ^(a) | - | If yes, equivalent power (W) | - | | | |
| | | Chromaticity coordinates (x and y) | 0,440 | | | |
| Parameters for directional light sources: | | | | | | |
| Peak luminous intensity (cd) | 660 | Beam angle in degrees, or the range of beam angles that can be set | 115 | | | |
| Parameters for LED and OLED light sources: | | | | | | |
| R9 colour rendering index value | 0 | Survival factor | 0,90 | | | |
| the lumen maintenance factor | 0,96 | | | | | |

(a)'-': not applicable; (b)'-': not applicable;

