

# FLOS

05.4380.OW Off-white

## Emi Table

Designed by Erwan Bouroullec, 2023




LED - LED array - 36.7W - 2959lm - 2700K - CRI> 90

Anti-glare appliance for installation on tables and coffee tables. Built-in 220-240 V power supply, with cable and plug. Spare parts for the optical module (lens) are available, please see the accessories. Independent control of the Up&Down lighting through Touch Dimming capacitive sensors in the top part of the central rod.

Are you a professional and your project needs consulting and support?

BOOK AN APPOINTMENT



### Main specifications

EAN	8424229003222
Mounting	Table
Environments	Indoor dry location
Light Source Type	LED
LED type	LED array
Lamp category	LED
Number of heads	1
Power (W)	36.7
System power (W)	43.5
Source flux (lm)	4174
System flux (lm)	2959

### Physical

Colour	Off-white
Orientation	Fixed
Cord colour	Black
Cord length (mm)	2500
Net weight (kg)	8.4
IP internal	20

### Download

Mounting instructions [↓ PDF](#)

### Photometric Files

LDT / IES [↓ ZIP](#)


### Technical Drawings

2D [↓ ZIP](#)

3D [↓ ZIP](#)



## Schematic light drawing



## Photometric

Lighting type	Total
Light distribution	Symmetric
CCT (K)	2700
CRI>	90
McAdam steps (SDCM)	3
Rf fidelity index	89
Rg gamut index	101
LED Life / Failure Ratio	L80B50>60.000h_Tc85°C
Extreme cut off	Yes

## Electrical

Insulation class	III
Frequency (Hz)	50/60
Main voltage (Vac)	220-240
LED current (mA)	760
Driver	Integrated
Dimmable	Yes
Dimming range (%)	1-100
Dimming interface	Dimmer Integrated

## Ecodesign and Energy Labelling

This product contains a light source of energy efficiency class E



Replaceable (LED only) light source by a professional



Replaceable control gear by an end-user

## Accessories & Power Supply



OPTIONAL  
Diffuser

Optical

08.0956.14

3 Lens Kit for Emi Ceiling Large,  
Emi Floor & Emi Table - Flood  
Optic



OPTIONAL  
Diffuser

Optical

08.0956.40

3 Lens Kit for Emi Ceiling Large,  
Emi Floor & Emi Table - Flood  
Optic