



lin base connect Design: IP44.DE

lin base connect Design: IP44.DE

Lichttechnik:
230V Power LED
2700K
L70/50.000 h

Anschluss:
5 m Zuleitung
(H05RN-F 3G0,75 mm²)
inkl. connect Stecker
5 m Zuleitung auf Anfrage
kürzbar

Montage:
Bauseitiges Fundament oder
befestigter Untergrund

Material:
Aluminiumguss
pulverbeschichtet
Sicherheitsglas klar

Schutzart:
IP65



Lichtrichtung:

light technology:
230V Power LED
2700K
L70/50.000 h

connection:
5 m supply cable
(H05RN-F 3G0,75 mm²)
incl. connect plug
5 m supply cable can be
shortened on request

assembly:
on site foundation or
solid ground

material:
aluminium die-casting
powder-coated
safety glass clear

protection class:
IP65



light direction:

	Farbe colour	Art.-Nr. item no.	Systemleistung system performance
lin 40 base 	anthracite RAL 7016	92093-27-AN-CO	9 W/164 lm
	cool brown	92093-27-CB-CO	9 W/164 lm
	deep black RAL 9005	92093-27-BL-CO	9 W/164 lm
lin 70 base 	anthracite RAL 7016	92090-27-AN-CO	18 W/328 lm
	cool brown	92090-27-CB-CO	18 W/328 lm
	deep black RAL 9005	92090-27-BL-CO	18 W/328 lm

Größe in mm
size in mm