## **Product Information Sheet**

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

sources	JELEGAI ED REGUI	LATION (EU) 2019/20	DIS with regard to energ	gy labelling of light
Supplier's name	e or trade mark:	LEDVANCE		
Supplier's addr	ess: LEDVANCE G	imbH, Parkring 33, G	Garching, Germany	
Model identifie	er: AC34670			
Type of light so	urce:			
Lighting techno	logy used:	LED	Non-directional or directional:	NDLS
Light source cap-type (or other electric interface)		constant current: 700 mA		
Mains or non-m	nains:	NMLS	Connected light source (CLS):	No
Colour-tuneable	e light source:	No	Envelope:	-
High luminance	light source:	No		
Anti-glare shield	d:	No	Dimmable:	No
		Product para	T	
Parameter		Value	Parameter	Value
up to the neare Useful luminor indicating if it r in a sphere (3 cone (120º) or i (90º)	oo h), rounded st integer us flux (φuse), efers to the flux 60º), in a wide n a narrow cone	3 000 in Sphere (360°)	Energy efficiency class  Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set  Standby power (Psb),	E 30006500
On-mode power (P <sub>on</sub> ), expressed in W		25,0	expressed in W and rounded to the second decimal	0,00
Networked standby power (P <sub>net</sub> ) for CLS, expressed in W and rounded to the second decimal		-	Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set	80
Outer dimensions	Height	796	Spectral power	See image
	Width	10	distribution in the	in last page
Outer	Height		or the range of CRI- values that can be set	

separate control gear, lighting control parts and non- lighting control parts, if any (millimetre)		range 250 nm to 800 nm, at full-load				
Claim of equivalent power <sup>(a)</sup>	-	If yes, equivalent power (W)	-			
		Chromaticity coordinates (x and y)	0,440			
Parameters for LED and OLED light sources:						
R9 colour rendering index value	0	Survival factor	0,90			
the lumen maintenance factor	0,96					

(a)'-': not applicable; (b)'-': not applicable;

