



**lin spike connect** Design: IP44.DE

## lin spike connect Design: IP44.DE

für unbefestigte Beet- und Grünflächen for unpaved beds and greens

**Lichttechnik:**  
230V Power LED  
2700K  
L70/50.000 h

**Anschluss:**  
5 m Zuleitung  
(H05RN-F 3G0,75 mm<sup>2</sup>)  
inkl. connect Stecker  
5 m Zuleitung auf Anfrage  
kürzbar

ortsveränderlich

**Material:**  
**Kopf + Lamellen:**  
Aluminiumguss  
pulverbeschichtet  
**Spieß: Edelstahl**  
pulverbeschichtet  
**Sicherheitsglas klar**

**Schutzart:**  
IP65



**Lichtrichtung:**



**light technology:**  
230V Power LED  
2700K  
L70/50.000 h

**connection:**  
5 m supply cable  
(H05RN-F 3G0,75 mm<sup>2</sup>)  
incl. connect plug  
5 m supply cable can be  
shortened on request

movable

**material:**  
**head + slats:**  
aluminium die-casting  
powder-coated  
**spike: stainless steel**  
powder-coated  
**safety glass clear**

**protection class:**  
IP65



**light direction:**



	Farbe colour	Art.-Nr. item no.	Systemleistung system performance
<b>lin 40 spike</b> 	anthracite RAL 7016	92094-27-AN-CO	9 W/164 lm
	cool brown	92094-27-CB-CO	9 W/164 lm
	deep black RAL 9005	92094-27-BL-CO	9 W/164 lm
<b>lin 70 spike</b> 	anthracite RAL 7016	92091-27-AN-CO	18 W/328 lm
	cool brown	92091-27-CB-CO	18 W/328 lm
	deep black RAL 9005	92091-27-BL-CO	18 W/328 lm

Größe in mm  
size in mm