## **Product Information Sheet**

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

	, , ,	_	
or trade mark:	LEDVANCE		
ess: LEDVANCE G	mbH, Parkring 33, G	Garching, Germany	
r: AC35681			
urce:			
ogy used:	LED	Non-directional or directional:	NDLS
-type	constant		
c interface)	current: 200 mA		
ains:	NMLS	Connected light source (CLS):	Yes
light source:	No	Envelope:	-
light source:	No		
l:	No	Dimmable:	Yes
	Product para	meters	
	Value	Parameter	Value
	General product p	arameters:	
00 h), rounded st integer us flux (φuse), efers to the flux 50°), in a wide	8 800 in Sphere (360°)	Energy efficiency class  Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the	3 000
ower (P <sub>on</sub> ),	8,0	can be set  Standby power (P <sub>sb</sub> ), expressed in W and rounded to the second decimal	0,00
ssed in W and	0,00	Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set	80
Height	206	Spectral power distribution in the	See image in last page
	r: AC35681  urce: logy used: lotype c interface) lains: light source: li	r: AC35681  urce: logy used: c interface) lains: light source: light sou	r: AC35681  urce: logy used: LED Non-directional or directional:  lotype constant current: 200 mA lains: NMLS Connected light source (CLS): light source: No Envelope: light source: No Dimmable:  Product parameters  Value Parameter  General product parameters:  Inption in on-  00 h), rounded st integer  Is flux (фuse), efers to the flux 500°), in a wide in a narrow cone in a narrow cone  Dower (Pon), 8,0 Standby power (Psb), expressed in W and rounded to the nearest 100 K, that can be set  Dower (Pon), Seed in W and second decimal descond decimal  dby power (Pnet) seed in W and second decimal descond decimal

separate control gear, lighting control parts and non- lighting control parts, if any (millimetre)		range 250 nm to 800 nm, at full-load		
Claim of equivalent power <sup>(a)</sup>	-	If yes, equivalent power (W)	-	
		Chromaticity coordinates (x and y)	0,434	
Parameters for LED and OLED light sources:				
R9 colour rendering index value	0	Survival factor	0,90	
the lumen maintenance factor	0,96			

(a)'-': not applicable; (b)'-': not applicable;

