



wittenberg 4.0 | wi4-ab-3e

AUFBAUSTRALER

Kompakte Bauform, filigranes Gehäuse, größte Gestaltungsvielfalt.

* Leuchtenserie sowohl für private Nutzung wie anspruchsvolle Spezialanwendungen



(Abb. exemplarisch)

Design: Jan Dinnebier, mawa / Engineering: mawa

Produkt- variante	Leistung in W ^{LED}	Abstrahlwinkel in Grad	Dimmungen Matchcode	Lichtfarben und Lichtstrom ^{LED} in Kelvin und Lumen
HighCRI	12,7 W	12°/ 24°/ 38°	-4, -7, -9	2700 K / 930 lm, 3000 K / 980 lm, 4000 K / 1100 lm
		(Wechseloptiken mittels Saugheber oder Silikonpad austauschbar)		(weitere Lichtfarben auf Anfrage)

Matchcode-Kürzel für Dimmungen: -2 Drehpotentiometer am Gehäuse / -4 DALI / -7 Phasen- und abschnitt / -9 Bluetooth






wittenberg 4.0 | wi4-ab-3e

AUFBAUSTRALER

Dimensionen:



- Farbe:**
- weiß matt (RAL 9016)
 - schwarz matt (RAL 9005)
 - individuelle RAL-Farben auf Anfrage

- Gehäuse:** Aluminium pulverbeschichtet weiß oder schwarz matt (individuelle RAL-Farben auf Anfrage)
- Kopf:** 365° dreh- und 90° schwenkbar | Ein Bajonettverschluss fixiert den Lichtkopf am Gehäuse und ermöglicht einen schnellen partiellen Austausch.
- Lichtquelle:** 3 × standard-LED (High CRI), Ra > 95 (typ. 98)
- Lebensdauer:** Standard-LED: L90 (10 k) > 61.000 h (IES LM-80 / TM-21)
- Betriebsgerät:** inklusive
- Betriebsbereich:** AC 220V–240V / 50Hz–60Hz
- Zubehör:** umfangreiches Zubehör – Wechseloptiken, LSD-Spezialdiffusoren, Wabenraster und Shutter – für fein abgestimmte Abstrahlwinkel und Lichtlenkung (siehe Zubehörübersicht unter mawa-design.de)
- Schutzklasse:** I
- Schutzart:** IP20
- Gewicht:** 1.440 g

LVK auf mawa-design.de unter Leuchten



wittenberg 4.0 | wi4-ab-3e

SURFACE-MOUNTED SPOTLIGHT

Compact dimensions, minimalist design and extensive design versatility.

* Luminaire series suitable for both private use and sophisticated specialized applications



(illustration exemplary)

Design: Jan Dinnebier, mawa / Engineering: mawa

Product variants	Performance in W ^{LED}	lenses with beam angle in degrees	Dimming Matchcode	Light colour and luminous flux ^{LED} in Kelvin and Lumen
HighCRI	12,7 W	12°/ 24°/ 38°	-4, -7, -9	2700 K / 930 lm, 3000 K / 980 lm, 4000 K / 1100 lm
		(exchangeable by means of vacuum cup or silicone pad)		(further light colours on request)

Dimming match code abbreviations: -2 Rotary potentiometer on housing / -4 DALI / -7 Phase-cut dimming / -9 Bluetooth






wittenberg 4.0 | wi4-ab-3e

SURFACE-MOUNTED SPOTLIGHT

Dimensions:



- Colour:**
- white matt (RAL 9016)
 - black matt (RAL 9005)
 - individual RAL colour on request

Housing: Aluminium housing powder-coated, white or black matt (individual RAL colours on request)

Spot light: 365° rotatable and 90° tiltable | A bayonet catch fastens the light head in the housing and allows for quick partial exchange.

LED modules: 3 × standard LED (High CRI), Ra > 95 (typ. 98)

Life time: Standard-LED: L90 (10 k) > 61.000 h (IES LM-80 / TM-21)

Control gear: included

Operating area: AC 220V–240V / 50Hz–60Hz

Accessories: Extensive range of accessories – interchangeable optics, LSD-special diffusers, honeycombs and shutters – available for finely tuned beam angles and light control
(See accessory overview at mawa-design.de)

Protection class: I

Degree of protection: IP20

Weight: 1.440 g

LDC on mawa-design.de under Lighting