# **FIFTY-FIFTY LAMP** COLLECTION

PRODUCT FACT SHEET



# FIFTY-FIFTY COLLECTION

DESIGN BY SAM WELLER, 2018

Named Fifty-Fifty after the lamp's counterweight system that creates equilibrium between the two parts, it is clear to see how Sam Weller's references to physics and engineering influence the design. Based on the idea of stripping a multi-purpose task light to its fundamental elements, Fifty Fifty balances refined, pared-back aesthetics with optimal functionality.


Configurable aluminium components minimise the overall complexity of the design and manufacturing process, creating a feature of the joints and mechanisms that is consistent throughout the entire series. The single cantilever arm is easy to tilt and pivot, featuring a touch-sensitive dimmer switch for precisely positioning and controlling the light source. The collection comprises table, wall and floor lamps.

#### HIGHLIGHTS


- · Part of a progressive and technologically advanced lighting collection.
- A family of multifunctional task lamps that can be used free standing, on a desk or placed on the floor.
- ·CE approved.
- ·Integrated LED light source ensuring a life span of at least 25,000 hours of use.
- ·Integrated touch step dimmer switch.
- $\cdot \textsc{Table}$  and floor lamps suitable for both private and office environments.
- Also available as a wall lamp that can be mounted on the wall with steel brackets.
- · Qualified for contract use.

· For indoor use only.


#### DIMENSIONS



FIFTY-FIFTY TABLE LAMP WITH TABLE BASE WIDTH 18,5 CM | 7.3" DEPTH 90 CM | 35.4" HEIGHT 60 CM | 23.6" MAX. ARM REACH 75 CM | 29.5"




FIFTY-FIFTY MINI TABLE LAMP WIDTH 16,5 CM | 6.5" DEPTH 65 CM | 25.6" HEIGHT 45 CM | 17.7" MAX. ARM REACH 50 CM | 19.7"



FIFTY-FIFTY FLOOR LAMP HEIGHT 135 CM | 53.1" LENGTH 90 CM | 35.4" WIDTH 25 CM | 9.8" MAX. ARM REACH 75 CM | 29.5"

# MATERIALS

LAMP BODY Extruded aluminium arms with die cast aluminium joints and head. TABLE LAMP BASE Die cast aluminium with internal sand cast iron counter weight. Powder coated steel base plate with foam pad protector.



FIFTY-FIFTY WALL LAMP WIDTH 7.5 CM | 3" DEPTH 187 CM | 73.6" HEIGHT 67 CM | 26.4"

FLOOR LAMP BASE Extruded aluminium tube with die cast aluminium inserts. Machined steel plate base plate with foam pad protector. WALL BRACKET Machined steel wall bracket and counterweight. CORD Black silicone cable.

# COLOUR & FINISH

Please note that the colour codes are indicative.

SHELL	SIZE	TABLE LAMP WITH TABLE BASE	MINI TABLE LAMP	FLOOR LAMP	FIFTY-FIFTY WALL	
SOFT BLACK RAL 9004		۰	٠	۰	٠	
ASH GREY RAL 7035		٠	٠			
CREAM WHITE RAL 9010					٠	

# FIFTY-FIFTY TABLE, MINI & FLOOR LAMP


#### **TECHNICAL SPECIFICATIONS**

LIGHT SOURCE	POWER (WATTS)	DIMMABLE	POWER SUPPLY	CORD LENGTH	SWITCH
Integrated LED	4W	Yes	220-240V AC at 50/60Hz UK/EU plug mounted adapter	200 cm	Touch step dimmer

#### **TEST SPECIFICATIONS\***

FLUX (LUMENS)	CCT (KELVIN)	CRI (1-100)			
360lm	3000k, warm white	85			
*Photometrics and the specifications shown are taken using the integrated LED light source fitted in the production luminaire.					

#### PHOTOMETRICS



## CERTIFICATES

CE APPROVED

This product has been assessed and complies with the essential requirements of the relevant European directives.



Tested according to the following european EN IEC standards which relate specifically to electrical lighting products including  $\cdot$  EN 55015:2013 (radio disturbance)

- · EN 61547:2009 (EMC immunity)
- · EN 61000-3-2:2014 (EMC compatibility)
- · EN 61000-3-3:2013 (EMC compatibility)
- · EN 60598-2-4:1997 (portable luminaires)
- · EN 60598-1:2015 (general requirements)
- · EN 62493:2010 (human exposure to EMC)

#### COUNTRY OF ORIGIN

China

## DOWNLOADS

Packshots and lifestyle photos, 2D / 3D files, care and maintenance, instructions, test certificates, product fact sheets, and product presentations are available in our Image Bank at hay.com.

#### LINK TO DIGITAL LIBRARY

# FIFTY-FIFTY WALL LAMP

#### TECHNICAL SPECIFICATIONS


LIGHT SOURCE	POWER (WATTS)	DIMMABLE	POWER SUPPLY	CORD LENGTH	SWITCH
Integrated LED	7.7W	Yes	220-240V AC at 50/60Hz UK/EU plug mounted adapter	300 cm	Touch step dimmer

# **TEST SPECIFICATIONS\***

FLUX (LUMENS)	CCT (KELVIN)	CRI (1-100)
700lm	3000k, warm white	85

\*Photometrics and the specifications shown are taken using the integrated LED light source fitted in the production luminaire.

#### PHOTOMETRICS



## CERTIFICATES

CE APPROVED

This product has been assessed and complies with the essential requirements of the relevant European directives.



Tested according to the following european EN IEC standards which relate specifically to electrical lighting products including

- EN 55015:2013 (radio disturbance)
- · EN 61547:2009 (EMC immunity)
- ·EN 61000-3-2:2014 (EMC compatibility)
- EN 61000-3-3:2013 (EMC compatibility) • EN 60598-2-4:1997 (portable luminaires)
- · EN 60598-2-4:1997 (portable luminalies)
- · EN 60598-1:2015 (general requirements)
- $\cdot\,\text{EN}$  62493:2010 (human exposure to EMC)

## COUNTRY OF ORIGIN

China

#### DOWNLOADS

Packshots and lifestyle photos, 2D / 3D files, care and maintenance, instructions, test certificates, product fact sheets, and product presentations are available in our Image Bank at hay.com.

LINK TO DIGITAL LIBRARY