Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

sources	LLLOAILD KLOOI	-AHON (LO) 2013/20	ors with regard to energ	gy labelling of light	
Supplier's name or trade mark: LEDVANCE					
Supplier's address: LEDVANCE GmbH, Parkring 33, Garching, Germany					
Model identifie	r: AC34673				
Type of light so	urce:				
Lighting technology used:		LED	Non-directional or directional:	NDLS	
Light source cap-type (or other electric interface)		constant current: 950 mA			
Mains or non-mains:		NMLS	Connected light source (CLS):	No	
Colour-tuneable light source:		No	Envelope:	-	
High luminance light source:		No			
Anti-glare shield:		No .	Dimmable:	No	
Product parameters					
Parameter		Value General product p	Parameter	Value	
Energy consur	nntion in on-	36	Energy efficiency	E	
Energy consumption in on- mode (kWh/1000 h), rounded up to the nearest integer		30	class	L	
Useful luminous flux (фuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)		4 400 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	30006500	
On-mode power (P _{on}), expressed in W		35,5	Standby power (P _{sb}), expressed in W and rounded to the second decimal	0,00	
Networked standby power (P _{net}) for CLS, expressed in W and rounded to the second decimal		-	Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set	80	
Outer	Height	1 196	Spectral power	See image	
dimensions without	Width	10	distribution in the	in last page	
without	Depth	1		 	

separate control gear, lighting control parts and non- lighting control parts, if any (millimetre)		range 250 nm to 800 nm, at full-load				
Claim of equivalent power ^(a)	-	If yes, equivalent power (W)	-			
		Chromaticity coordinates (x and y)	0,440			
Parameters for LED and OLED light sources:						
R9 colour rendering index value	0	Survival factor	0,90			
the lumen maintenance factor	0,96					

(a)'-': not applicable; (b)'-': not applicable;

