## **Product Information Sheet**

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark: LEDVANCE Supplier's address: LEDVANCE GmbH, Parkri Model identifier: AC34587  Type of light source:  Lighting technology used: LED  Light source cap-type consta current: 50  (or other electric interface) NMLS  Colour-tuneable light source: No  High luminance light source: No  Anti-glare shield: No	Non-directional or directional:  Int  OO mA  S
Model identifier: AC34587  Type of light source:  Lighting technology used:  Light source cap-type (or other electric interface)  Mains or non-mains:  Colour-tuneable light source:  No High luminance light source:  No Anti-glare shield:  NO34587  LED  Constance  Constance  Current: 50  NMLS  NO	Non-directional or directional:  Int  OO mA  S
Type of light source:  Lighting technology used:  Light source cap-type (or other electric interface)  Mains or non-mains:  Colour-tuneable light source:  No High luminance light source:  No Anti-glare shield:	directional:  ont ont ont ont ont ont ont ont ont on
Lighting technology used:  Light source cap-type (or other electric interface)  Mains or non-mains:  Colour-tuneable light source:  High luminance light source:  No Anti-glare shield:  No	directional:  ont ont ont ont ont ont ont ont ont on
Light source cap-type constact current: 50 Mains or non-mains: NML:  Colour-tuneable light source: No High luminance light source: No Anti-glare shield: No	directional:  ont ont ont ont ont ont ont ont ont on
(or other electric interface)  Mains or non-mains:  Colour-tuneable light source:  High luminance light source:  No Anti-glare shield:  No	S Connected light Yes source (CLS):  Envelope: -  Dimmable: No  ct parameters  Parameter Value
Mains or non-mains:  Colour-tuneable light source:  No High luminance light source:  No Anti-glare shield:  No	source (CLS):  Envelope:  Dimmable:  No  ct parameters  Parameter  Value
High luminance light source: No Anti-glare shield: No	Dimmable: No  ct parameters  Parameter Value
Anti-glare shield: No	ct parameters Parameter Value
	ct parameters Parameter Value
	Parameter Value
Produ	
Parameter Value	advat a anamatana
	oduct parameters:
Energy consumption in on- mode (kWh/1000 h), rounded up to the nearest integer	Energy efficiency E class
Useful luminous flux (φuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)	rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set
On-mode power (P <sub>on</sub> ), 19,0 expressed in W	Standby power (P <sub>sb</sub> ), 0,00 expressed in W and rounded to the second decimal
Networked standby power (P <sub>net</sub> ) 0,00 for CLS, expressed in W and rounded to the second decimal	Colour rendering 80 index, rounded to the nearest integer, or the range of CRI-values that can be set
Outer Height 82	Spectral power See image
dimensions Width 82	distribution in the in last page
without Depth 82	

separate control gear, lighting control parts and non- lighting control parts, if any (millimetre)		range 250 nm to 800 nm, at full-load		
Claim of equivalent power <sup>(a)</sup>	-	If yes, equivalent power (W)	-	
		Chromaticity coordinates (x and y)	0,456	
Parameters for LED and OLED light sources:				
R9 colour rendering index value	0	Survival factor	0,90	
the lumen maintenance factor	0,97			

(a)'-': not applicable; (b)'-': not applicable;

