BELL PORTABLE LED





Taking its name from a classic dome shape, Bell is an exercise in reductionism. The hyper-polished surface allows Bell to take on the tone and characteristics of its surroundings while a concealed diffuser produces its soft lighting. Bell Portable LED offers up to 9 hours of battery life.

Year of Design 2021
Product Weight 1.40kg
Finishing Process Gloss Painted
Power Method Rechargeable

Power Method Rechargeable
Battery Operating Time Approx 7-9 hours
Battery Charging Time Approx 5 hours

Cable Spec AWM 2464 22AWG VW-1 1A 80 °C 300V Cable Type/Length USB-A to Magnetic, 200 cm

Light Source3W LEDMax Wattage3WLumens160CRI>90Colour Temperature3000K

Dimmability Touch Dimmable

Voltage 5V Environment Indoor, IP44

Spares LEDPB02, POBAT01, POMC01
Certification/Electrical Class T20, Certiÿed for NZ/AUS

SILVER Code

BLACK

Shade Material

Base Material

Service Offer

Base Colour/Finish

Code

Code BEPO01SSUN
Shade Material Acrylonitrile B

Shade Colour/Finish Black, Gloss

Shade Material Acrylonitrile Butadiene

Styrene (ABS)

BEPO01BLUN

Black, Gloss

New

Acrylonitrile Butadiene Styrene (ABS)

Acrylonitrile Butadiene Styrene (ABS)

Shade Colour/Finish Silver, Mirrored

Base Material Acrylonitrile Butadi

Material Acrylonitrile Butadiene Styrene (ABS)

Base Colour/Finish Silver, Polished

Service Offer New







BELL PORTABLE LED





Taking its name from a classic dome shape, Bell is an exercise in reductionism. The hyper-polished surface allows Bell to take on the tone and characteristics of its surroundings while a concealed diffuser produces its soft lighting. Bell Portable LED offers up to 9 hours of battery life.

2021 Year of Design **Product Weight** 1.40kg **Finishing Process** Plated Rechargeable **Power Method** Approx 7-9 hours **Battery Operating Time**

Battery Charging Time Approx 5 hours AWM 2464 22AWG VW-1 1A 80 °C 300V Cable Spec

Cable Type/Length USB-A to Magnetic, 200 cm

Light Source 3W LED Max Wattage 3W Lumens 160 >90 **Colour Temperature** 3000K

Dimmability Touch Dimmable

Voltage

Indoor, IP44 **Environment**

LEDPB02, POBAT01, POMC01 **Spares Certification/Electrical Class** T20, Certiÿed for NZ/AUS









GOLD

Code BEPO01GOUN **Shade Material** Acrylonitrile Butadiene

Styrene (ABS)

Shade Colour/Finish Gold, Mirrored **Base Material** Acrylonitrile Butadiene Styrene (ABS)

Base Colour/Finish Gold, Polished

Service Offer New

COPPER

Code BEPO01COUN

Shade Material Acrylonitrile Butadiene

Styrene (ABS)

Shade Colour/Finish Copper, Mirrored

Acrylonitrile Butadiene **Base Material**

Styrene (ABS)

Base Colour/Finish Copper, Polished

Service Offer New

19/7.5"