


PLUTO

3W | 240 lm | 2700K

PLUT-3W-2700K-E14-NT


Pluto 3W 2700K E14 Non-Tinted LED Bulb

tala®



PHYSICAL

Bulb diameter:	45 mm
Bulb length:	72 mm
Glass shape:	G45
Base:	E14
Materials:	glass and nickel
Glass finish:	Clear
Weight:	16g
Max. working temp.:	Max. 40°C
IP rating:	IP54




ELECTRICAL

Power:	3W
Current:	0.01 A
Voltage:	220-240V~ V
Frequency:	50/60Hz
Power factor:	0.9
Efficiency:	80 lm/W
Lifetime:	30000 hrs

ILLUMINATION

CCT:	2700K
Lumens:	240 lm
Incandescent equiv.:	24W
Flicker:	<5%
Beam angle:	360°
Light source:	LED
CRI:	95Ra
R9:	65
TM30 - Rg	100
TM30 - Rf	90

IES/LDT photometry files
and product photography
available on request



DIMMING

Dimmable 0-100%
Recommended dimmer: Varilight V-Pro
(For a full list of recommended and compatible dimmers see website)

Tala Energy Ltd. 25b Vyner Street,
London, E2 9DG, United Kingdom

Tala Europe B.V. Bertus Aafjeshove 40
Nieuwegein 3437 JN

WARRANTY

2 years

tala.co.uk | hello@tala.co.uk | +44 7700 170343

EAN

5061046292052

Specification subject to change without
notice. Refer to our website for the most
recent product documentation. Tala
designs in the EU/UK are protected by
registered and or unregistered design rights