MELT CONE FAT TABLE LED







ON

OFF

Melt is evocative of molten glass, the interior of a melting glacier or images of deep space. An imperfect, organic and naturalistic light that produces a mesmerizing hot-blown glass effect. Melt is created through a process of blow moulding and vacuum metallisation to achieve melted orbs with abundant and unusual luminosity. Here the orb sits on a cone shaped base creating a striking silhouette.

Year of Design **Product Weight Finishing Process Power Method Cable Spec** Cable Type/Length **Light Source** Max Wattage Lumens CRI **Colour Temperature** Dimmability Voltage Environment Spares **Certification/Electrical Class**

2021 1.70kg Semi-Metallised, Powder Coated Mains SPT-2, 2x18AWG, 300 V Black Fabric, 250cm 6W LED 9W 800 >90 3000K Inline Dimmable 100-240V Indoor LEDRING02A, LEDTC01UN T20, Certiÿed for NZ/AUS





SILVER

Code Shade Code Shade Material Shade Colour/Finish Base Code Base Material Base Colour/Finish Service Offer	MES02CH-TUN01M1 MES02CH Polycarbonate Silver, Mirrored CONT01-TUN01M1 (1 X CONT01BKUN; 1 X LEDTC01UN) Steel Black, Gloss New
GOLD Code	MES02GO-TUN01M1

Code	MES02GO-TUN01M1
Shade Code	MES02GO
Shade Material	Polycarbonate
Shade Colour/Finish	Gold, Mirrored
Base Code	CONT01-TUN01M1
	(1 X CONT01BKUN;
	1 X LEDTC01UN)
Base Material	Steel
Base Colour/Finish	Black, Gloss
Service Offer	New



MELT CONE FAT TABLE LED







ON

OFF

Melt is evocative of molten glass, the interior of a melting glacier or images of deep space. An imperfect, organic and naturalistic light that produces a mesmerizing hot-blown glass e¢ect. Melt is created through a process of blow moulding and vacuum metallisation to achieve melted orbs with abundant and unusual luminosity. Here the orb sits on a cone shaped base creating a striking silhouette.

Year of Design **Product Weight Finishing Process Power Method Cable Spec** Cable Type/Length **Light Source** Max Wattage Lumens CRI **Colour Temperature** Dimmability Voltage Environment Spares Certification

2021 1.70kg Semi-Metallised, Powder Coated Mains SPT-2, 2x18AWG, 300 V Black Fabric, 250cm 6W LED 9W 800 >90 3000K Inline Dimmable 100-240V Indoor LEDRING02A, LEDTC01UN T20, Certiÿed for NZ/AUS





COPPER

Service Offer

Code Shade Code Shade Material Shade Colour/Finish Base Code Base Material Base Colour/Finish	MES02CO-TUN01M1 MES02CO Polycarbonate Copper, Mirrored CONT01-TUN01M1 (1 X CONT01BKUN; 1 X LEDTC01UN) Steel Black, Gloss
Service Offer	New
SMOKE	
Code	MES02SM-TUN01M1
Shade Code	MES02SM
Shade Material	Polycarbonate
Shade Colour/Finish	Silver, Mirrored
Base Code	CONT01-TUN01M1 (1 X CONT01BKUN; 1 X LEDTC01UN)
Base Material	Steel
Base Colour/Finish	Black, Gloss

New

181/294 25/9.5"