Floor & Table LIGHTING

MELT PORTABLE LED





OFF





ON

Melt Portable LED expands the collection, oŽering the same mesmerizing hot-blown glass eŽect within a portable design. Melt is evocative of molten glass, the interior of a melting glacier or images of deep space. Melt Portable LED is available in a wide range of ÿnishes and oŽers up to 10 hours of battery life.

2021 Year of Design **Product Weight** 0.45kg

Finishing Process Semi Metallised, Painted

Power Method Rechargeable **Battery Operating Time** Approx 8-10 hours **Battery Charging Time** Approx 5 hours

Cable Spec AWM 2464 22AWG VW-1 1A 80 °C 300V

Cable Type/Length USB-A to Magnetic, 200 cm

Light Source 2.5W LED Max Wattage 2.5W Lumens 100 >90 CRI 3000K **Colour Temperature**

Touch Dimmable Dimmability

Voltage

Environment Indoor, IP44 Spares

LEDPB01, POBAT01, POMC01 **Certification/Electrical Class** T20, Certiÿed for NZ/AUS









BLACK

Code MEPO01BKUN

Shade Material Polyethylene Terephthalate

(PET)

Shade Colour/Finish Silver, Mirrored **Base Material** Acrylonitrile Butadiene

Styrene (ABS)

Base Colour/Finish Black, Gloss

Service Offer New

SILVER

Code MEPO01SSUN

Shade Material Polyethylene Terephthalate

(PET)

Shade Colour/Finish Silver, Mirrored **Base Material** Acrylonitrile Butadiene

Styrene (ABS)

Base Colour/Finish Silver, Polished

Service Offer New

13/5"

LIGHTING Floor & Table

MELT PORTABLE LED



Melt Portable LED expands the collection, oœering the same mesmerizing hot-blown glass eœectwithin a portable design. Melt is evocative of molten glass, the interior of a melting glacier or images of deep space. Melt Portable LED is available in a wide range of ÿnishes and oœers up to 10 hours of battery life.

Year of Design 2021 Product Weight 0.45kg

Finishing Process Semi-Metallised, Plated

Power Method Rechargeable
Battery Operating Time Approx 5 hours

Approx 5 hours

Cable Spec AWM 2464 22AWG VW-1 1A 80 °C 300V

Cable Type/Length USB-A to Magnetic, 200 cm

Light Source2.5W LEDMax Wattage2.5WLumens100CRI>90Colour Temperature3000K

Dimmability Touch Dimmable

Voltage 5

Environment Indoor, IP44
Spares LEDPB01, POE

SparesLEDPB01, POBAT01, POMC01Certification/Electrical ClassT20, Certiÿed for NZ/AUS



GOLD

Code MEPO01GOUN

Shade Material Polyethylene Terephthalate

(PET)

Shade Colour/Finish Gold, Mirrored
Base Material Acrylonitrile Butadiene

Styrene (ABS)

Base Colour/Finish Gold, Polished

Service Offer New

COPPER

Code MEPO01COUN

Shade Material Polyethylene Terephthalate

(PET)

Shade Colour/Finish Copper, Mirrored

Base Material Acrylonitrile Butadiene

Styrene (ABS)

Base Colour/Finish Copper, Polished

Service Offer New

